

PLFY-WP-VBM-E

4-WAY CASSETTE



Technical specifications

MODEL			PLFY-WP32VBM-E	PLFY-WP40VBM-E	PLFY-WP50VBM-E
Power Supply			1 phase 220-240V, 50Hz		
Cooling capacity		kW	3.6	4.5	5.6
		Btu/h	12300	15400	19100
Heating capacity		kW	4	5	6.3
		Btu/h	13600	17100	21500
Power input	Cooling	kW	0.04	0.04	0.05
	Heating	kW	0.03	0.03	0.04
Current	Cooling	A	0.35	0.35	0.45
	Heating	A	0.28	0.28	0.38
External finish			Galvanized steel plate		
Dimensions	HxLxD	mm	258x840x840	258x840x840	258x840x840
Net weight		kg	22	22	22
Heat exchanger			Cross fin (Al fin and Cu pipe)		
Fan	Type x n.		Turbo fan x 1		
	Air flow (low-mid-high)	m ³ /min	13-14-15-16	13-14-15-16	13-14-17-19
	Ex Static pressure	Pa	0	0	0
Motor	Type		Motor DC		
	Power output	kW	0.05	0.05	0.05
Air filter			PP honeycomb fabric		
Water pipe diameter	Inlet/Outlet		Rc 3/4 screw		
Local drain pipe diameter			OD 32	OD 32	OD 32
Sound pressure (low-mid-high)	Measured in anechoic chamber	dB(A)	27-29-30-31	27-29-30-31	27-30-32-34